



# PORTABLE HOT WATER PRESSURE WASHER

**DIRECT DRIVE / GAS DRIVEN / DIESEL FIRED**



**Adjustable thermostat**  
up to 93°C/200°F with illuminated rocker switch

**Heavy-duty 6,000 PSI**  
rupture disk

Heavy-duty **roll-cage powder coated 1.5" OD** steel tube frame, with centre balanced lift hook (above industry standards)

**Lifting hook**

**Vanguard 200** recoil w/ 20amp charge

**HEATING COIL**

1/2" Heavy-duty schedule 80 American made Carbon Steel Cold-rolled pipe, no weak points from heating to make bends

5,500PSI Rated, "Full Sized" 80' length for maximum heat rise and proper heat production

**Stainless-steel coil skin** provides extra durability and resists corrosion

**12v Wayne burner** with low voltage inhibitor, prevents burner from starting up if battery voltage is low

Direct drive AR triplex pump carries a **5-year warranty**

**12" oil drain hose** on engine for ease of maintenance

**22 L/6 gal removable, rust-proof polyethylene fuel tank**

**Brake assembly**

**12" heavy-duty flat free tires**

**Marine sealed battery** box with AGM deep cycle battery



**3/4" HD Threaded**  
mount axle

**TMR / TRUCK MOUNT READY**

**FEATURES**

- 36" gun wand assembly with insulated grip and quick connects
- 50' x 3/8" high-pressure, twin wire braided hose with quick connects
- Adjustable low-pressure chemical injector assembly with quick connects
- 4 color-coded quick connect spray nozzles
- 1 color-coded quick connect chemical nozzle

**WARRANTY**

ENGINE.....	3 YEARS
PUMP.....	5 YEARS
ACCESSORIES..	90 DAYS
FRAME.....	LIFETIME
COIL.....	3 YEARS
MODEL # HW2765VA	



**DIRECT DRIVE**

MODEL	GPM	PSI	CC	ENGINE	BTU/HR	PUMP MODEL	DRIVE	BURNER FUEL CONS.	UNIT DIMENSIONS	SHIPPING DIMENSIONS	SHIP WT (lbs)
HW2765VA	3	2,700	203	VANGUARD 200	300,000	TRIPLEX AR RCV3G27-F7	DIRECT DRIVE	1.23 GPH	40"L x 28"W x 42"H	37"L x 29"W x 48"H	480



# PORTABLE HOT WATER PRESSURE WASHER ACCESSORY OPTIONS

## ACCESSORY OPTIONS

<b>500195</b>	HOSE REEL - 360° PIVOT, 150' MAX LENGTH, 300° F (STEAM RATED SWIVEL) COMES WITH WHIP HOSE
<b>59.400.001</b>	360° HOSE REEL SWIVEL BRACKET
<b>85.205.090</b>	ADJUSTABLE PRESSURE INSULATED DUAL LANCE W/GUN
<b>85.490.016</b>	SOOT REMOVER, 125 ML (4 OZ)
<b>85.490.015</b>	FUEL STABILIZER, 236.6 ML (8 OZ)
<b>85.210.135</b>	ROTARY NOZZLE, 3.5 ORIFICE, 5,000 PSI
<b>59.400.004</b>	7" RAIN CAP / EXHAUST CHIMNEY
<b>85.403.009</b>	20" STAINLESS STEEL WHIRL-A-WAY, 4000 PSI, 300° F
<b>85.403.010</b>	24" STAINLESS STEEL WHIRL-A-WAY, 4000 PSI, 300° F

## HOSE REEL FEATURES

- **Hose Capacity:** 150' x 3/8"
- **Hose Axle:** Stops hose from kinking when attached to hose reel axle. Eliminates wear on hose, for longer life
- **Adjustable Friction Brake:** Eliminates hose backlash when unwinding
- **Heavy-Duty Performance:** Super Swivel rated to 5,000 PSI & 325°F standard
- **Easy Push/ Pull Spring Loaded Lock Pin:** Prevents unwanted hose unwinding
- **Multi-Position Collar w/ Spring Loaded Lock Pin:** Allows reel to be positioned in a variety of positions and locked
- **Durable Construction:** Heavy gauge cold rolled metal. Durable reel, capable of securely storing high pressure hose.
- **Easy Turn Handle:** Prevents fatigue when coiling your hose
- **Hose Guide -** Allows for easy hose rolling & prevents tangling
- **Double Bearing Design w/ Stainless Steel Shaft:** Prevents side movement and allows reel to swivel freely
- **Locking Collar Shaft:** Prevents reel from sliding out of the bracket vertically
- **Smooth Radius Bent Arm:** Eliminates 90° bend and strengthens the arm



500195



SWIVEL REEL



59.400.001



85.205.090



85.210.135



85.490.016



85.490.015



59.400.004



85.403.009



85.403.010